

Tec
A



Ref: A02152 PENETRATING LUBRICANT 500ML KING

Effective penetrating lubricant

- ✓ Anti-corrosion
- ✓ Multi-position valve
- ✓ No damage to components



SPECIFICATIONS

Density: 0.81 +/- 0.02

Odour: Hydrocarbon

APPLICATION

Removes rust and all deposits.

No damage to metal, rubber or wood.

Inflammable packaging gas (co2).

Product strips and degreases, leaving anti-corrosion film after evaporation.

The product has a low pour point. It quickly penetrates and disintegrates corroded mass such as rust, thus loosening components.

Multi-position valve for hard-to-reach areas.

RECOMMENDED FOR

- All doors
- Joints, bolts, gears
- Automobile, aviation and maritime industries

INSTRUCTIONS FOR USE

Shake well before use.

Spray directly on components to be treated.

Leave to take effect for 30 minutes.

PACKAGING

Presentation: Aerosol 500mL

Pack size: Carton of 12

White iron can Diameter: 65mm/Height: 195mm

Nominal volume: 650ml /Net volume 500ml

Pallet size: 1,080 units – 90 cartons

REGULATIONS

FOR INDIVIDUAL AND PROFESSIONAL USE.

Dangerous. Highly flammable aerosol

Follow precautions for use.

Refer to the safety data sheet (SDS). Available on request.

Our data sheets are prepared with current knowledge and subject to modifications. Photo nonbinding
16/11/2018 Index 3.1