



Ref.: A11013 COPPER LUBRICANT 500ML PUCK

Lubricates and protects metal parts with copper content.

- ✓ Reduces wear
- ✓ Non-drying, non-evaporating
- ✓ High resistance to heat

APPLICATION

Resists salt corrosion, water and steam. Does not dry or evaporate. Reduces wear and friction of metallic parts by placing a neutral film between two different types of metal.

Heat-resistant up to 1,100°C

Use for mechanics: mounting shafts and bearings, construction of pneumatic equipment and concrete pumps; for automotive: tailpipe, sump and cylinder head gaskets.

RECOMMENDED FOR

- Electric equipment,
- screwed assemblies, nuts and bolts, steam joints, cable glands, mechanical parts,
- welding machine bearings, high-temperature valves, foundry ejectors, easy opening steel ladle nozzles, rotary nozzles and sliding gates in steelworks, aluminum extrusion (start before refractory coating), Zamak mold release,
- furnace hinges, power transmissions (hot chains), lubricating cables.
- Glass industry, brickyards, mounting turbine pins.

INSTRUCTIONS FOR USE

Shake well until you hear the ball bearing clearly to mix the product before use. Spread in threads with a brush.

Touch-dry: several minutes

Hardens: 12 hours

PACKAGING

Packaging unit: Aerosol 500ml

Pack size: Box of 12 units

Tin can Diameter: 65mm/Height: 195mm

Nominal volume: 650ml /Net volume 500ml

Pallet size: 1080 units – 90 boxes

REGULATIONS

FOR INDIVIDUAL AND PROFESSIONAL USE

Dangerous. Follow precautions for use.

Refer to the safety data sheet (SDS). Available on request.

Our data sheets are prepared with current knowledge and are subject to modifications. Photo non-binding.

06/11/2018 Index 3.1