

# SILICONE GREASE

Ref. A25358 - 500 ml

**QUICK**  
TECH

GREASING



For thorough greasing and preventing metal parts from drying out

- High-performance lubricant
- Multi-position nozzle
- Odorless



## APPLICATION

Highly viscous silicone that penetrates and strongly adheres to any material.

Colorless and dense grease with high lubricating performance. Water repellent and weather-resistant.

This grease prevents plastic and rubber from drying out.

Its active ingredient is chemically inert and odorless after application.

### Specific uses:

- mounting, pre-greasing, and protecting seals
- greasing mechanisms that are sprayed with or immersed in water
- as a waterproof and anti-drying coating for rubber
- protecting machined parts from corrosion

### Specifications:

- Usage temperatures (continuous): -20°C to +140°C.
- The aerosol spray can be used in any position.
- Spray nozzle with extension tube for precise application and use in hard-to-reach areas.

## RECOMMENDED FOR

- Construction, building, plastics industries
- Assembly lines
- Garages
- Plastics industry
- Textiles industry

## PACKAGING

Packaging unit (PU): Aerosol can

Sales unit (SU):  
Box of 6 units

Pallet size:  
1260 units - 105 boxes

Tin can diameter  
65 mm/height 195 mm

Nominal volume: 650 ml -  
Net volume: 500 ml

## INSTRUCTION

Clean the surface to be greased. Shake well until you clearly hear the bead. Spray evenly until required absorption reached. Wait a few moments for the grease to perfectly stick to the surface before mounting or returning to use.

## REGULATIONS

FOR PROFESSIONAL USE ONLY.  
Hazardous. Follow precautions for use.

*Refer to the safety data sheet (SDS), available upon request.  
Our data sheets are prepared using current knowledge and are subject to modifications.  
Photo non-binding. 01/01/2024 Index 1.0*

**S.I.C.O.**

577 Rue du Pommarin B.P. 16 - Voreppe - 38341 Moirans CEDEX France  
Tel: +33 (0)4 76 50 85 50 / sico.commercial@sico.fr / www.sico.fr